



KONICA MINOLTA

AccurioPrint
C4065

BUILD YOUR BRIDGE TO SUCCESS

RETHINK VERSATILITY



Giving Shape to Ideas

ACCURIOPRINT C4065 SPECIFICATIONS

RETHINK OPTIONS

AccurioPrint C4065

Type	Console
Color availability	Color
Scanning resolution	600 dpi x 600 dpi
Writing resolution	Equivalent to 3600 dpi x 2400 dpi
Copy Speed	A4 Simplex: 66 ppm/Duplex: 66 ppm
	A3 Simplex: 37 ppm/Duplex: 37 ppm/
	217-360 g/m2 45 A4/26 A3
Gradation	256
Paper Sizes	330.2 x 487.7 mm 330.2 x 860 mm (max.duplex) 330.2 x 1300 mm (max. simplex)
Standard Paper TrayCapacity	1500 sheets A4 80 gsm
Magnification	25 – 400%, in 0.1% steps
Memory size	16 GB
Warm-up Time	390 seconds or less
First Copy/Printing Time (Color/Monochrome)	6.1 seconds or less/
	4.0 seconds or less
Scan speed (A4)	Single- sided 140 opm ⁹³ Duplex 280 opm ⁹¹
Envelope Printing	Standard
Controller CPU- IC 607	IC-607: Intel Pentium G4400 3.3 GHz ⁹¹
Main Unit Size (WxDxH) mm	84.65 x 35.55 x 58.19 inches (2,150 x 903 x 1478 mm) (main unit + DF-713 + LU-202m + FS-532+IC
Power consumption	3840 W or less(Main body)
Duty Cycle	7,02,000 ²
Average Monthly Print Volume (optimum volume)	upto 30 K

KONICA MINOLTA IMAGE CONTROLLER IC-607

Architecture	Internal
OS	Linux
CPU	Intel Pentium C4400
Clock speed	3.3 GHz
RAM std	16 GB
HDD	2 TB (2 x 1TB)
Page-description language	Adobe® PostScript® 3; PDF v1.7; TIFF (v6); PPML v2.2
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

FIERY IMAGE CONTROLLER IC-419

Architecture	Internal
OS	Linux
CPU	Intel® Pentium® Processor G4400
Clock speed	3.3 GHz
RAM std	8 GB
HDD	500 GB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, Microsoft Office document formats: doc, docx, xls,xlsx, ppt, pptx, pub (via Hot Folders)
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

DF-713 — DUAL SCAN DOCUMENT FEEDER (OPTION)

Tray Capacity	300 sheets (80 gsm)		
Original Weight Duplex	50 – 210 gsm		
Detectable Document Size	Min: 100 x 140 mm Max: 297 x 432 mm		
Scan Speed by Resolution	200 dpi	Colour: Simplex 140 ipm Monochrome: Simplex 140 ipm	Duplex 280 ipm Duplex 280 ipm
	300 dpi	Colour: Simplex 120 ipm Monochrome: Simplex 120 ipm	Duplex 240 ipm Duplex 240 ipm
Scan Speed by Resolution	400 dpi	Colour: Simplex 100 ipm Monochrome: Simplex 100 ipm	Duplex 200 ipm Duplex 200 ipm
	600 dpi	Colour: Simplex 75 ipm Monochrome: Simplex 80 ipm	Duplex 150 ipm Duplex 160 ipm

OPTIONS

KM Image Controller	IC-607
EFI Internal Controller	IC-419
Paper Feeding Unit	PF-602m
Dehumidifier heater	HT-504
Paper feeding unit	PF-707m
Dehumidifier heater	HT-506
PFU connection Kit	FA-502
Large capacity feeding unit	LU-202m
Dehumidifier heater for LU	HT-503
Envelope printing guide for LU	MK-746
Large capacity feeding unit (banner)	LU-202Xlm
Multi bypass feeding	MB-508
Banner Paper Feeder kit	MK-760
Multi bypass tray	MB-509
Intelligent Media Sensor	IM-101
Output Tray	OT-511
Stapling Unit	FS-532m
Saddle Stitcher Kit	SD-510
Punch Kit	PK-525
Post Inserter Kit	PI-502
Output Tray Unit	OT-512
Long Sheet Kit (Output)	MK-761
Intelligent Quality Optimiser	IQ-501

–All specifications refer to A4-size paper of 80 gsm quality.

–The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

–Some of the product illustrations contain optional accessories.

–Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

–Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.

–All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

–⁹¹When using KM when using IC-607

–⁹²Peakvolume in Q Zone

–⁹³When using DF-713, 200 dpi

Konica Minolta Business Solutions India Pvt. Ltd.

Building No: 8, Tower-C, 10th Floor, DLF Cyber City, Phase-2, Gurugram, Haryana-122002, India | Board No. +91-124-6652000

URL: www.konicaminolta.in | marcom@bin.konicaminolta.in

Connect with us:    