
# LARGE FORMAT PRINTER SURECOLOR™ SC-P10070/P20070





One good printing experience is all it takes to set new standards. The Epson SureColor™ SC-P10070 and SC-P20070 are professional production printers designed for the best results. Advanced PrecisionCore™ MicroTFP printhead technology yields high speeds of up to 17.5 m<sup>2</sup>/h\*, with accurate dot placement for stand-out visuals. To top it off, the Epson UltraChrome™ PRO nine-colour pigment ink system develops vibrant prints with lasting durability and the high-precision media feeding system ensures smooth, reliable operations.









Handling



1.5mm



SC-P10070



SC-P20070



## **ENGINEERED FOR BUSINESS**

### **Swift Speeds For Maximum Output**

New PrecisionCore MicroTFP printhead utilises 8000 nozzles, for class-leading print speeds of up to 17.5 m<sup>2</sup>/h\*.

#### **Affordable Prints With Peace of Mind**

The UltraChrome PRO ink with four levels of grey produces brilliant prints that last up to 200 years. Costeffective 700 ml ink cartridges ensure low printing costs.

### **Precision Media Feeding System**

Maximum output with Realtime Media Adjustment & Feedback System, a Media Inductive Roller System and a unique Roll Media Skew Reduction System.





Model Number

SC-P10070



Model Number	SC-P10070	SC-P20070	
Printer Width	44"	64"	
Printing Technology	-		
Printhead	PrecisionCore™ MicroTFP Printhead		
Printing Method	Nozzle Verification System		
Nozzle Configuration	Black colour ink: 4,000 nozzles (PK, MK, DGY, GY, Li	GV 800 nozzles each colour)	
VOZZIO GOTINGUI AUGIT		,	
Dist Disseller	Colour ink : 4,000 nozzles (C, VM, Y, LC, VLM 800 nozzles each colour)		
Print Direction	Bi-directional printing, uni-directional printing		
	Auto Head Alignment technology		
rint Quality			
Maximum Resolution	2400x1200 dpi		
finimum Ink Droplet Volume	3.5pl		
erformance*1			
raft Mode	600 x 600dpi, 1.9 minutes		
ormal Mode	1200 x 1200dpi, 3.0 minutes		
ne Mode	2400 x 1200dpi, 5.6 minutes		
k System	-		
k Type	Epson UltraChrome™ PRO Ink		
olours	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Dark Grey, Grey, Light Grey, Light Cyan,		
olodis			
	Vivid Light Magenta		
k Capacity			
rinter Software on CD-ROM			
Printer Driver	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later / Mac	OSX10.6.8 or later	
	Windows Server 2003 Standard/Standard *64bit, 2008 Standard/Standard *64bit /R2, 2012 or later		
	2003/2003 *64bit, 2008/2008R2 *64bit/2012 or later	(Certification/Logo: Windows Server 2008/2008R2)	
aper Handling	-		
aper Feed Method	Friction Feed		
oll Dimensions	170mm		
aper Size & Thickness	Roll paper : 254mm (10") - 1118mm (44")	Roll paper : 254mm (10") - 1626mm (64")	
aper Oize & Trilottiess			
	Cut sheet : 210mm (A4)- 1118mm (44") 0.08-1.50mm		
orderless	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++),	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++),	
	406mm(16in.), 432mm(17in./USC), 508mm(20in.),	406mm(16in.), 432mm(17in./USC), 508mm(20in.),	
	515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+),	515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+),	
	728mm(29in./B1), 841mm(A0), 914(36in./A0+),	728mm(29in./B1), 841mm(A0), 914(36in./A0+),	
	1030mm(B0), 1118mm(44in/B0+)	1030mm(B0), 1118mm(44in/B0+), 1270mm(50in.),	
		1372mm(54), 1524(60in.)	
oll Paper Remaining	The remaining amount is managed by the barcode pri	int on Roll paper.	
ontrol Panel			
olour & Size	2.7" Colour LCD		
umber of Dots	960 x 240 pix.		
	960 x 240 pix.		
onnectivity			
tandard	Hi-Speed USB		
thernet	1000BASE-T (Recommended) / 100BASE-TX		
ontrol Code	ESC/P raster		
lemory	<del>-</del>		
- 1ain	1GB	1.5GB	
oftware			
C Software	User's Guide(EN) Network Guide(EN), LFP RemoteP	anel 2 EpsonColorCalibration Itility EpsonNet Setup	
1 O COITWAIG	EpsonNet Config, EpsonNet Print (Windows only)		
rintor Moh Eustein			
rinter Web Function	'Remote Manager' HDD utility - Control of HDD functi		
oftware from Web Download	LFP Accounting Tool (Job monitoring, consumable co	st tracking), HDD Utility software (Web download)	
lectrical Specifications			
oltage	AC100-240V 50/60Hz		
ated Current	5A		
ower Consumption	Operating: Approx. 95W; Sleep: Approx. 2.8W *Interfa	ace is 1000BASE-T; Power off (Stand-by): Less than 0.5\	
ecommended Operating	<u> </u>	·	
Temperature	Operating: 10°C - 35°C; Storage: -20°C - 40°C		
•		% 85% (no condensation)	
Humidity	Operating: 20% - 80% (no condensation); Storage: 5	// 00 // (110 00110G115dt1011)	
coustic Noise Level			
ound Pressure Level	Approx 50.5dB (A)	Approx 51.1dB (A) less than	
	Approx 65.3dB (A)	Approx 67dB (A) less than	
Sound Power Level	ME 1 VDAE 1 (7/0/04/00/04/3)		
Sound Power Level System Requirement	Windows XP/Vista/7/8/8.1 (32/64bit) or later		
	CPU: Core 2 Duo 3.05GHz; Memory: Memory more	than 1GB; HDD: Free space more than 32GB	
		than 1GB; HDD : Free space more than 32GB	

SC-P20070





\*1 Figures represent print times only for Epson test sample image (A1 size) as shown, produced on Premium Photo paper.



A1:588×735mm

#### Ink Cartridge Compatibility

#### 700 ml Ink Cartridges

700 mi ink Cartridges		
<ul> <li>Photo Black</li> </ul>	C13T809100	
<ul><li>Cyan</li></ul>	C13T809200	
<ul> <li>Magenta</li> </ul>	C13T809300	
<ul><li>Yellow</li></ul>	C13T809400	
<ul><li>Light Cyan</li></ul>	C13T809500	
<ul> <li>Vivid Light Magenta</li> </ul>	C13T809600	
<ul> <li>Dark Grey</li> </ul>	C13T809700	
<ul> <li>Matte Black</li> </ul>	C13T809800	
<ul><li>Grey</li></ul>	C13T809900	
<ul><li>Light Grey</li></ul>	C13T809000	

### **Supplies & Optional Accessories**

Auto Cutter Spare Blade	C13S210040		
Cleaning Stick	C13S090013		
Maintenance Box	C13T619300		
Auto Take-up Reel Unit	C12C932201		
Roll Adapter	C12C932231		
Adobe® PostScript® 3™			
Expansion Unit	C12C891131		
Hard Disk Unit	C12C848031		



©2016 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing Printed June 2016

To find out more, visit www.epson.com.my/largeformat or call 1800-8-17349 (Toll-free)

